Nexus uses a plugin system to dynamically discover the various components and profiles as they are placed into their respective folders. The `nexus_profiles` folder holds the YAML definitions for the agent.

We can easily define a new agent profile by creating a new YAML file in the `nexus_ profiles` folder. Listing 7.7 shows an example of a new profile with a slightly updated persona. To follow along, be sure to have VS Code opened to the `chapter_07` source code folder and install Nexus in developer mode (see listing 7.7). Then, create the `fiona.yaml` file in the `Nexus/nexus/nexus_base/nexus_profiles` folder.

Listing 7.7 `fiona.yaml` (create this file)

```
agentProfile:
  name: "Finona"
  avatar: " "     #1
  persona: "You are a very talkative AI that
↪ knows and understands everything in terms of
↪ Ogres. You always answer in cryptic Ogre speak."    #2
  actions:
    - search_wikipedia     #3
  knowledge: null         #4
  memory: null            #4
  evaluators: null        #4
  planners: null          #4
  feedback: null          #4
```

#1 The text avatar used to represent the persona
#2 A persona is representative of the base system prompt.
#3 An action function the agent can use
#4 Not currently supported

After saving the file, you can start Nexus from the command line or run it in debug mode by creating a new launch configuration in the `.vscode/launch.json` folder, as shown in the next listing. Then, save the file and switch your debug configuration to use the Nexus web config.

Listing 7.8 `.vscode/launch.json` (adding debug launch)

```
{
      "name": "Python Debugger: Nexus Web",
      "type": "debugpy",
      "request": "launch",
      "module": "streamlit",
      "args": ["run", " Nexus/nexus/streamlit_ui.py"]      #1
    },
```

#1 You may have to adjust this path if your virtual environment is different.