6. *Calculate the total score.* For our rubric, we'll average the score for all criteria to provide a total score.
7. *Ensure evaluation consistency.* The technique we'll use for evaluation will provide very consistent results.
8. *Review, revise, and iterate.* We'll review, compare, and iterate on our profiles, rubrics, and the evaluations themselves.

Table 9.2 Rubric ratings

Rating	Description
1	Poor alignment: this is the opposite of what is expected given the criteria.
2	Bad alignment: this isn't a good fit for the given criteria.
3	Mediocre alignment: it may or may not fit well with the given criteria.
4	Good alignment: it may not align 100% with the criteria but is a good fit otherwise.
5	Excellent alignment: this is a good recommendation for the given criteria.

This basic rubric can now be applied to evaluate the responses for our profile. You can do this manually, or as you'll see in the next section, using a second LLM profile.

9.6 Grounding evaluation with an LLM profile

This section will employ another LLM prompt/profile for evaluation and grounding. This second LLM prompt will add another block after the recommendations are generated. It will process the generated recommendations and evaluate each one, given the previous rubric.

Before GPT-4 and other sophisticated LLMs came along, we would have never considered using another LLM prompt to evaluate or ground a profile. You often want to use a different model when using LLMs to ground a profile. However, if you're comparing profiles against each other, using the same LLM for evaluation and grounding is appropriate.

Open the `recommender_with_LLM_evaluation\flow.dag.yaml` file in the prompt flow visual editor, scroll down to the `evaluate_recommendation` block, and click the `evaluate_recommendation.jinja2` link to open the