```
    {
        "title": " The Butterfly Effect
        "subject": "5",
        "format": "5",
        "genre": "4"
    },
    {
        "title": " Primer",
        "subject": "5",
        "format": "5",
        "genre": "4"
    },
    {
        "title": " Time Bandits",
        "subject": "5",
        "format": "5",
        "genre": "5"
    }
```

The output of this `parsing_results` block now gets passed to the output and is wrapped in a list of recommendations. We can see what all this looks like by running the flow.

Open `flow.dag.yaml` for the flow in the visual editor, and click the Play (Run All) button. Be sure to select to use both recommender variants. You'll see both variations run and output to the terminal.

At this point, we have a full working recommendation and LLM evaluation flow that outputs a score for each criterion on each output. However, to do comprehensive evaluations of a particular profile, we want to generate multiple recommendations with various criteria. We'll see how to do batch processing of flows in the next section.

9.7.2 Running batch processing in prompt flow

In our generic recommendation profile, we want to evaluate how various input criteria can affect the generated recommendations. Fortunately, prompt flow can batch-process any variations we want to test. The limit is only the time and money we want to spend.

To perform batch processing, we must first create a JSON Lines (JSONL) or JSON list document of our input criteria. If you recall, our input criteria looked like the following in JSON format: