Listing 10.1 `question-answer-prompting` flow

```
   Inputs:
        context  : the content to ask the question about
        question : question asked specific to the content
        expected : the expected answer

   LLM: Question-Answer (the prompt used to ask the question)
        inputs:
               context and question
        outputs:
               the prediction/answer to the question

   Embeddings: uses an LLM embedding model to create the embedding
representation of the text

     Embedding_predicted: embeds the output of the Question-Answer LLM
     Embedding_expected: embeds the output of the expected answer

   Python: Evaluation (Python code to measure embedding similarity)
     Inputs:
            Embedding_predicted output
            Embedding_expected output
     Outputs:
            the similarity score between predicted and expected

   Outputs:
        context: -> input.context
        question: -> input.question
     expected: -> input.expected
     predicted: -> output.question_answer
     evaluation_score: output.evaluation

### Example Output
{
    "context": "Back to the Future (1985)…",
    "evaluation_score": 0.9567478002354606,
    "expected": "Marty traveled back in time 30 years.",
    "predicted": "Marty traveled back in time 30 years from 1985 to 1955
in the movie \"Back to the Future.\"",
    "question": "How far did Marty travel back in time in the movie
Back to the Future (1985)"
}
```

Before running this flow, make sure your LLM block is configured correctly. This may require you to set up a connection to your chosen LLM. Again, refer to chapter 9 if you need a review on how to complete this. You'll need to configure the LLM and `Embedding` blocks with your connection if you're not using OpenAI.

After configuring your LLM connection, run the flow by clicking the Play button from the visual editor or using the Test (Shift-F5) link in the YAML editor window. If everything is connected and configured correctly, you should see output like that in listing 10.1.