You may note that the solution to figure 10.3 is also provided as an example in listing 10.8. It's also helpful to go back and review listing 10.7 for the reply from the LLM about the problem. From this, you can see the reasoning steps the LLM applied to get its final answer.

Now, we can look at the prompt that evaluates how well the solution solved the problem. Open `evaluate_answer.jinja2`, shown in listing 10.9, to review the prompt used. The prompt is simple, uses zero-shot prompting, and allows the LLM to generalize how it should score the expected and predicted. We could provide examples and scores, thus changing this to an example of a few-shot classification.

Listing 10.9 `evaluate_answer.jinja2`

```
system:

Please confirm that expected and predicted results are
the same for the given problem.     #1
Return a score from 0 to 1 where 1 is a perfect match and 0 is no match.
Please just return the score and not the explanation.     #2

user:
Problem: {{problem}}     #3

Expected result: {{expected}}     #4

Predicted result: {{predicted}}     #5
```

#1 The rules for evaluating the solution
#2 Direction to only return the score and nothing else
#3 The initial problem statement
#4 The expected or grounded answer
#5 The output from the CoT prompt earlier

Looking at the LLM output shown earlier in listing 10.7, you can see why the evaluation step may get confusing. Perhaps a fix to this could be suggesting to the LLM to provide the final answer in a single statement. In the next section, we move on to another example of prompt reasoning.

10.2.2 Zero-shot CoT prompting

As our time travel demonstrates, CoT prompting can be expensive in terms of prompt generation for a specific class of problem. While not as effective, there are techniques similar to CoT that don't use examples and