can be more generalized. This section will examine a straightforward phrase employed to elicit reasoning in LLMs.

Open `prompt_flow/zero-shot-cot-prompting/flow.dag.yaml` in the VS Code prompt flow visual editor. This flow is very similar to the previous CoT, as shown in figure 10.4. The next lsting shows the YAML pseudocode that describes the flow.

Listing 10.10 `zero-shot-CoT-prompting` flow

```
Inputs:
     statement  : the statement problem to be solved
     expected : the expected solution to the problem

LLM: cot (the prompt used to solve the problem)
     inputs: statement
     outputs: the predicted answer given the problem statement

LLM: evaluate_answer (the prompt used to evaluate the solution)
     inputs:
            statement: -> input.statement
            expected: -> input.expected
            predicted: -> output.cot

      outputs: a score of how well the problem was answered


 Outputs:
     statement: -> input.statement
     expected: -> input.expected
     predicted: -> output.cot
     evaluation_score: output.evaluate_answer

 ### Example Output
{
    "evaluation_score": "1",     #1
    "expected": "After the final jump, ↪
       ↪ Max finds himself in the year 1980 and
he is 75 years old.",     #2
    "predicted": "Max starts in… ↪
       ↪ Therefore, after the final jump, ↪
       ↪ Max is 75 years old and in the year 1980.",     #3
    "statement": "In a complex time travel …"     #4
}
```

#1 The final evaluation score
#2 The expected answer
#3 The predicted answer (the steps have been omitted showing the final answer)
#4 The initial problem statement

Run/test the flow in VS Code by pressing Shift-F5 while in the visual editor. The flow will run, and you should see output similar to that shown