Listing 2.6 Chat completions response

```
{
    "id": "chatcmpl-8WWL23up3IRfK1nrDFQ3EHQfhx0U6",
    "choices": [                                          #1
        {
            "finish_reason": "stop",
            "index": 0,
            "message": {
                "content": "… omitted",
                "role": "assistant",       #2
                "function_call": null,
                "tool_calls": null
            },
            "logprobs": null
        }
    ],
    "created": 1702761496,
    "model": "gpt-4-1106-preview",     #3
    "object": "chat.completion",
    "system_fingerprint": "fp_3905aa4f79",
    "usage": {
        "completion_tokens": 78,     #4
        "prompt_tokens": 48,         #4
        "total_tokens": 126          #4
    }
}
```

#1 A model may return more than one response.
#2 Responses returned in the assistant role
#3 Indicates the model used
#4 Counts the number of input (prompt) and output (completion) tokens used

It can be helpful to track the number of *input tokens* (those used in prompts) and the *output tokens* (the number returned through completions). Sometimes, minimizing and reducing the number of tokens can be essential. Having fewer tokens typically means LLM interactions will be cheaper, respond faster, and produce better and more consistent results.

That covers the basics of connecting to an LLM and returning responses. Throughout this book, we'll review and expand on how to interact with LLMs. Until then, we'll explore in the next section how to load and use open source LLMs.

2.2 Exploring open source LLMs with LM Studio

Commercial LLMs, such as GPT-4 from OpenAI, are an excellent place to start to learn how to use modern AI and build agents. However, commercial agents are an external resource that comes at a cost, reduces