NOTE The examples in this section can be found in the `simplequestion` package if no package is explicit in the snippet.

3.2.1 A simple question

If you run the `SimpleQuestion` app from the solutions repository, you can see two types of results. The order of parsing—and therefore the output—are not always the same, and neither are the results, but there are only two kinds of results. The first is the *happy path*, where everything is going well: each worker completes its task on time, and the manager registers that completion. This output shows a `Success` in response to each request to parse:

```
[Worker$] - worker-text-c: done
[Manager$] - text-c parsed by worker-text-c
[Worker $] - worker-text-a: done
[Manager$] - text-a parsed by worker-text-a
[Worker $] - worker-file-b: done
[Manager$] - text-b parsed by worker-text-b
```

The second kind of result is the *unhappy path*, when parsing a text takes longer than is acceptable. In the following output, `text-c` takes more than 3 seconds, while the other two texts are processed in a timely manner:

```
[Worker $] - worker-text-a: DONE!                                    ❶
[Manager$] - text-a read by worker-text-a                            ❶
[Worker $] - worker-text-b: DONE!                                    ❶
[Manager$] - text-b read by worker-text-b                            ❶
[Manager$] - parsing text-c' has failed with [Ask timed out on
➥[Actor[akka://example-ask-without-content/user/manager-1/
➥worker-text-c#-1664156553]] after [3000 ms]. Message of type
➥[ask.simple.Worker$Parse]. A typical reason for
➥`AskTimeoutException` is that the recipient actor
➥didn't send a reply.                                               ❷
[Worker $] - worker-text-c: DONE!                                    ❷
```