`Worker.Parse`, which is equivalent to `ActorRef[Worker.Response]) => Worker.Parse`. That brings us full circle to the `createRequest` signature in `ask`.

For completeness, here are the remaining parameters. Feel free to skip to the next section if you've had enough technical details and would rather get back to the example. The `mapResponse` defines the callback as `Success` or `Failure`, depending on whether the response arrives on time. You already know this, but let's take a closer look. `mapResponse: Try[Res] => T` reads as follows:

- `mapResponse` is a function that needs to define two functions: one with the input `Success[Res]` and the output `T`, and another with the input `Failure` and the output `T`.
- In this example, `Res` is `Worker.Done` and `T` is `Manager.Command`. The `Try[Res] => T` expresses that after receiving the `Worker.Done` (wrapped in a `Success` or a `Failure`), the callback produces a `Manager.Command`. This command is the message the callback sends back to the manager; here, it is a `Report`.
- The `implicit responseTimeout: Timeout` is the amount of time the request waits for a response.

As you now know, because it is an implicit argument, if there is an implicit value in the scope, it will be used without having to be passed explicitly. There are many scopes in Scala, but we won't go into that here. (For more info, see chapter 42 of *Get Programming with Scala* by Daniela Sfregola; Manning, 2021, www.manning.com/books/get-programming-with-scala.)