Let’s see this in action by running the `AsyncLogSpec` test from listing 4.3. All you need to remember is that this spec proves that a `SimplifiedManager` logs “it’s done” when it receives a `SimplifiedManager.Log` message. You can run the test by executing the following:

```
sbt "chapter04/testOnly **.AsyncLogSpec"
```

This produces the following output:

```
10:42:13.844 DEBUG AsyncLogSpec - Starting ActorTestKit                ❶
10:42:13.964 INFO logging.SimplifiedManager$ - it's done               ❶
10:42:14.094 INFO akka.actor.CoordinatedShutdown -                     ❶
Running CoordinatedShutdown with reason [ActorSystemTerminateReason]   ❶
[info] AsyncLogSpec:
[info] a Simplified Manager
[info] - must be able to log 'it's done'
[info] Run completed in 740 milliseconds.
[info] Total number of tests run: 1
[info] Suites: completed 1, aborted 0
[info] Tests: succeeded 1, failed 0, canceled 0, ignored 0, pending 0
[info] All tests passed.
[success] Total time: 1 s, completed
```

❶ Noise

In this scenario, the first three lines are noise because all tests passed. To avoid this noise, you need to capture the logs. You can do that by adding the following logging configuration, which includes a `CapturingAppender` and a `CapturingAppenderDelegate` from the Akka test kit and the usual `ConsoleAppender` you can use in every JVM application. The `CapturingAppender` captures the test logs. If a test fails, the `CapturingAppenderDelegate` flushes the captured logs