into its `appender-ref` (here, `STDOUT`), which is output to the console according to the `ConsoleAppender`:

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>

    <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
        <encoder>
            <pattern>[%date{ISO8601}] [%level] [%logger] [%marker]
            ➥[%thread] - %msg</pattern>
        </encoder>
    </appender>

    <appender name="CapturingAppender"
    ➥class="akka.actor.testkit.typed.internal.CapturingAppender"/>

    <logger name="akka.actor.testkit.typed.internal.CapturingAppenderDelegate">
      <appender-ref ref="STDOUT"/>
    </logger>

    <root level="DEBUG">
        <appender-ref ref="CapturingAppender"/>
    </root>
</configuration>
```

With the previous configuration, you don't get the noisy log statements. However, to get the logs when the tests fail, you need to add the `LogCapturing` property to your spec, as follows:

```
class AsyncLogSpec
    extends ScalaTestWithActorTestKit
    with AnyWordSpecLike
    with Matchers
    with LogCapturing       ❶
```

❶ Adds the LogCapturing trait to print the logs when the test fails

With these two things in place, if all the tests pass, you get nothing but the result of the tests. And if a test fails, you get all the logs.