```
  def apply(databaseUrl: String): Behavior[Command] =
    supervisorStrategy {                                                    ❶
      Behaviors.setup[Command] { context =>
        // creates connection using databaseUrl
        Behaviors
          .receiveMessage[Command] {
            case Line(t, m, mt) =>
              ...                                                           ❷
              ... #B                                                        ❸
          }
          .receiveSignal {
            case (_, PostStop) =>
              ...                                                           ❶
            case (_, PreRestart) =>
              ...                                                           ❶
          }
      }
    }

  def supervisorStrategy(behavior: Behavior[Command]): Behavior[Command] = ❹
    Behaviors
      .supervise {
        Behaviors
          .supervise(behavior)
          .onFailure[UnexpectedColumnsException]
          .SupervisorStrategy.resume
      }
      .onFailure[DbBrokenConnectionException](SupervisorStrategy
        .restartWithBackoff(minBackoff = 3, maxBackoff = 30, randomFactor = 0.1)
        .withResetBackoffAfter(15))
}
```

❶ Closes the connection

❷ Transforms the line to a database schema that may raise an UnexpectedColumnsException

❸ Saves to the database, which may raise a DbBrokenConnectionException

❹ Composed supervision strategy

If the database connection breaks, the database writer is re-created. The database writer creates a new connection in `.setup` using the `databaseUrl`. The restart waits a few seconds to avoid any database writer accessing the database when the database is unresponsive and probably overloaded. For the same reason, the