Note that a photo's URL cannot reach a `PhotoProcessor` actor until at least one is registered.

You can put all this together and prove that a photo processor receives photos from a camera by running a test like the following.

Listing 6.3 Testing that the camera distributes the load evenly

```
class RoutingExamplesSpec
  extends ScalaTestWithActorTestKit
  with AnyWordSpecLike
  with Matchers
  with LogCapturing {

"a group router" should {
    "send messages to all photo processors registered" in {
      val photoProcessor1 = TestProbe[String]
      val pp1Monitor = Behaviors.monitor(
           photoProcessor1.ref, PhotoProcessor()) ❶

      val photoProcessor2 = TestProbe[String]
      val pp2Monitor = Behaviors.monitor(
           photoProcessor2.ref, PhotoProcessor()) ❶

      system.receptionist ! Receptionist.Register(PhotoProcessor.Key,
      ➥spawn(pp1Monitor))
      system.receptionist ! Receptionist.Register(PhotoProcessor.Key,
      ➥spawn(pp2Monitor))

      val camera = spawn(Camera())
      camera ! Camera.Photo("A")                ❷
      camera ! Camera.Photo("B")                ❷

      photoProcessor1.receiveMessages(1)        ❸
      photoProcessor2.receiveMessages(1)        ❹
    }
```

❶ Intercepts messages to the photo processor

❷ Sends photos

❸ Each photo processor receives a message