The only state you can set under these circumstances is `WeaklyUp`.

Let's see what happens if one of the seed nodes crashes without the possibility of shutting it down properly. This can be simulated by killing the process.

NOTE Under Linux or macOS, you can kill a process with `kill -9 [PID]`. On Windows 10, you can use `taskkill /F /PID [pid_number]`. You can find this PID by searching a Java process with the parameters `-jar [.../.../]sbt-launch.jar` and `-DPORT=2551` if you try to kill node 1 of the previous example.

Here is the output of the terminal running seed node 2 when seed node 1 is abruptly terminated:

```
Cluster Node [akka://words@127.0.0.1:2552] - Marking node as UNREACHABLE
➥[Member(akka://words@127.0.0.1:2551, Up)].                    ❶
Cluster Node [akka://words@127.0.0.1:2552] - is the new leader among
➥reachable nodes (more leaders may exist)                      ❷
```

❶ Seed node 1 becomes unreachable.

❷ Node 2 becomes the leader.

Seed node 1 is marked as `UNREACHABLE` by the cluster, thanks to a failure-detection mechanism that decides when a node should be considered unreachable.

The seed node was in an `Up` state when it crashed, but this can happen in any state. The node marked as `UNREACHABLE` must be shut down in this scenario because there is no way back. It cannot