topics/tree/main/chapter08b. You can find the contents of any snippet or listing in the .scala file with the same name as the class, object, or trait.

The following listing shows how an actor subscribes to `.setup`, defines its behavior to handle these `ClusterDomainEvents`, and unsubscribes when it receives a `PostStop` signal.

Listing 8.5 Subscribing to cluster domain events

```
import akka.actor.typed.PostStop
import akka.actor.typed.scaladsl.Behaviors
import akka.cluster.typed.{ Cluster, Subscribe, Unsubscribe }
import akka.cluster.ClusterEvent._
import akka.cluster.MemberStatus

object ClusterDomainEventListener {

  def apply() = Behaviors.setup[ClusterDomainEvent] { context =>
    Cluster(context.system).subscriptions ! Subscribe(
      context.self,
      classOf[ClusterDomainEvent])                                    ❶

    Behaviors
      .receiveMessage[ClusterDomainEvent] {                           ❷
        case MemberUp(member) =>
          context.log.info(s"$member UP.")
          Behaviors.same
        case MemberExited(member) =>
          context.log.info(s"$member EXITED.")
          Behaviors.same
        case MemberRemoved(m, previousState) =>
          if (previousState == MemberStatus.Exiting) {
            context.log.info(s"Member $m gracefully exited, REMOVED.")
          } else {
            context.log.info(s"$m downed after unreachable, REMOVED.")
          }
          Behaviors.same
        case UnreachableMember(m) =>
          context.log.info(s"$m UNREACHABLE")
          Behaviors.same
        case ReachableMember(m) =>
          context.log.info(s"$m REACHABLE")
          Behaviors.same
        case event =>
```