```
sbt:chapter08b>runMain example.countwords.CounterApp aggregator 2556
sbt:chapter08b>runMain example.countwords.CounterApp aggregator 2557
```

Executing each one from a different terminal would launch four application nodes: one seed node, one director, and two aggregators. Since the master can't do anything without the workers, it makes sense for the master to be moved to Up only when the cluster has a certain minimum number of worker nodes. You can use the configuration to set the minimum number of members with a particular role as a prerequisite for becoming Up. This configuration file defines a list of local seed nodes running on 127.0.0.1 and ports 2551, 2552, and 2553; since 2551 is the first seed node, this is sufficient to start the cluster.

Listing 8.8 Configuring the minimum number of worker nodes for `MemberUp`

```
...
cluster {
    seed-nodes = [
    "akka://WordsCluster@127.0.0.1:2551",
    "akka://WordsCluster@127.0.0.1:2552",
    "akka://WordsCluster@127.0.0.1:2553",
    ]
    role {
      seed.min-nr-of-members = 1          ❶
      aggregator.min-nr-of-members = 2    ❶
    }
}
example.countwords {
  workers-per-node = 5                    ❷
  delegation-parallelism = 20             ❸
}
...
```

❶ Number of node members required for any node to be moved to Up

❷ Number of workers in each aggregator node

❸ Number of texts to be pulled from the lag queue and distributed to the workers