This configuration specifies that at least two aggregators and one seed must be `Joining` before they can be moved to `Up`. You must also subscribe to the `SelfUp` cluster domain event to defer the guardian spawning the master.

If the guardian is created in a director node, two actors are created when `SelfUp` is received: a group router and a master that uses this router to delegate work to workers at random (the router's default strategy). If the guardian is created in an aggregator node—for example, with `runMain example.countwords.App worker 2556`—it spawns as many workers as are defined in the configuration value `example.countwords.workers-per-node`.

## Listing 8.9 Guardian setup and registration

```
import akka.cluster.Cluster
import akka.actor.typed.scaladsl.{ Behaviors, Routers }
import akka.actor.typed.{ ActorSystem, Behavior }
import com.typesafe.config.ConfigFactory

object CountWordsApp {

  def main ...

  def startup(role: String, port: Int): Unit = ...

  private object ClusteredGuardian {

    def apply(): Behavior[SelfUp] =
      Behaviors.setup[SelfUp] { context =>
        val cluster = Cluster(context.system)
        if (cluster.selfMember.hasRole("director")) {                    ❶
          Cluster(context.system).subscriptions ! Subscribe(             ❷
            context.self,
            classOf[SelfUp])
        }
        if (cluster.selfMember.hasRole("aggregator")) {                  ❸
          val numberOfWorkers =                                          ❹
```