NOTE You can find these IDs in the value of `akka.actor.serialization-identifiers` in the reference.conf files of the Akka modules.

If you use a SerDe that is not defined in Akka, the custom SerDe must have an `event_ser_id` value higher than `40`. This is defined by the `identifier` in the SerDe (see http://mng.bz/mVmW).

The tags created in the `tags` database are related to the events (see table 9.2). Because these tags can be joined in a database query with the previous table, such as

```
event_tag.event_id = event_journal.ordering
```

a reader can consume only the events for specific tags, increasing the overall capacity for parallelism. In chapter 10, you learn how to consume the journal to produce different views using queries like selecting containers that hold a specific cargo.

Table 9.2 Events in the `event_tag` table

event_id	tag
1	container-tag-0
2	container-tag-0
3	container-tag-2

Summary

- Akka Sharding allows you to distribute actors evenly in a cluster and address them by ID, leaving the location and relocation to the underlying mechanism.
- Akka Persistence gives you the ability to store the state of an actor in an event-sourcing fashion instead of using the standard approach of storing state by updating the previous state. With an event-sourcing approach, each change is stored as an entry in a ledger, always appending instead of updating. This way, you keep the history of all changes.
- Akka Persistence provides an interface based on commands and events you define with the command handler and the event handler. Each command triggers a function in the actor that can raise an event, which is usually stored in the database and changes the actor's state. This cycle is repeated for each received message.
- It's recommended that you add tags to events to provide parallelism when reading the journal. You can define the retention strategy for snapshotting and a supervision strategy to handle failure on persist.
- Serialization is necessary to store the events. Otherwise, the journal cannot be deserialized and thus cannot be read.