❺ References the database to use

❻ References the database to use

❼ Database reference configuration

❽ Profile used for the database connection; uses the Slick library

For more details on the configuration, see the reference.conf file of the akka-persistence and akka-persistence-jdbc projects.

Let's continue the example from chapter 9: you have containers to which you can add cargo of different types and sizes. In this example, three pieces of cargo are added: two to one container and the third to another. The events in table 10.2 show the entries in the journal.

Table 10.2 Events from the table `journal_events`

ordering	persistence_id	sequence_number	deleted	event_ser_id	event_ser_manifest	event_paylo
1	spcontainer-type-key|9	1	FALSE	33	example.persistence.SPContainer$CargoAdded	Binary data
2	spcontainer-type-key|9	2	FALSE	33	example.persistence.SPContainer$CargoAdded	Binary data
3	spcontainer-type-key|11	1	FALSE	33	example.persistence.SPContainer$CargoAdded	Binary data

To get all the IDs of the persistent entities of this journal, you can create a stream by calling the API method `persistenceIds`. It outputs the following:

```
spcontainer-type-key|9
spcontainer-type-key|11
```

To do this, you need a `ReadJournal` implementation such as `JdbcReadJournal`. The `ReadJournal` is the API for reading the entities' stored persistent events, and the `JdbcReadJournal` is the Akka implementation for JDBC-compliant databases to interact with Postgres, MySQL, Oracle, H2, and SQL Server. You can get one instance of `JdbcReadJournal` via the `PersistenceQuery`, which requires an `ActorSystem` and the ID of your implementation of choice of the `ReadJournal`. Once you have the instance, you can query the journal IDs.

Listing 10.4 Test to print a list of IDs

```
import akka.stream.scaladsl.Source
import akka.persistence.query.PersistenceQuery
import akka.persistence.jdbc.query.scaladsl.JdbcReadJournal
import akka.NotUsed

object Main extends App {

  implicit val system = ActorSystem(Behaviors.ignore, "runner")

  val readJournal: JdbcReadJournal = PersistenceQuery(system)          ❶
    .readJournalFor[JdbcReadJournal](JdbcReadJournal.Identifier)
```