`ShardedDaemonProcess` in an Akka cluster. Starting this cluster triggers the `ShardedDaemonProcess`, which creates three `LoggerBehavior`s in a node. To keep things simple, this behavior logs `tag-1`, `tag-2`, or `tag-3` when created, depending on the order of creation. (You can read how this is executed in the README.md.)

As soon as the first node starts, it generates the following output:

```
[INFO] [example.shardeddeamon.LoggerBehavior$] [] [LoggerSharded-
➥akka.actor.default-dispatcher-3] - spawned LoggerBehavior tag-2
[INFO] [example.shardeddeamon.LoggerBehavior$] [] [LoggerSharded-
➥akka.actor.default-dispatcher-25] - spawned LoggerBehavior tag-1
[INFO] [example.shardeddeamon.LoggerBehavior$] [] [LoggerSharded-
➥akka.actor.default-dispatcher-5] - spawned LoggerBehavior tag-3
```

Then you can add another node to the cluster to trigger a rebalance and get the following output from the original node:

```
[INFO] [akka.cluster.sharding.DDataShardCoordinator] [] [LoggerSharded-
➥akka.actor.default-dispatcher-25] - sharded-daemon-process-tagger:
➥Starting rebalance for shards [0]. Current shards rebalancing: []
```

In the logging of the new node, you eventually read that the `LoggerBehavior` `tag-1` is rebalanced to this new node:

```
[INFO] [example.shardeddeamon.LoggerBehavior$] [] [LoggerSharded-
➥akka.actor.default-dispatcher-5] - spawned LoggerBehavior tag-1
```

The idea is that with three nodes, you have one `ShardedDaemonProcess` in each with one `LoggerBehavior`. The following configuration from the file shardeddeamon.conf suffices. It is similar to what you've seen so far.

**Listing 10.9 `ShardedDaemon` cluster conf.iguration**

```
akka {
  actor {
    provider = cluster                          ❶
  }
  remote {
    artery {
      canonical.hostname = "127.0.0.1"          ❷
    }
  }
  cluster {
    seed-nodes = [                              ❸
      "akka://MiniCluster@127.0.0.1:25251",
      "akka://MiniCluster@127.0.0.1:25252"]
  }
}
```

❶ Provider

❷ Hostname

❸ Seed-nodes

`LoggerBehavior` does only one thing. It logs the `tag` you pass to it when initializing and then ignores any message: