Let's recap. To create a projection, pass an `ActorSystem`, a `CargosPerContainerRepository`, and an `indexTag` to the `createProjectionFor` method, which creates the read and write sides. To shard the projections, use the `ShardedDaemonProcess`.

The main idea is to use the `ShardedDaemonProcess` to spawn the `CargosPerContainerProjection`. But note that you can't spawn a projection inside the `ShardedDaemonProcess`; only a behavior can be spawned. So you have to wrap the projection in a `ProjectionBehavior`.

Listing 10.11 Initializing projections through a `ShardedDaemonProcess`

```
import akka.actor.typed.ActorSystem

import akka.cluster.sharding.typed.ShardingEnvelope

import akka.cluster.sharding.typed.ShardedDaemonProcessSettings
import akka.cluster.sharding.typed.scaladsl.ShardedDaemonProcess

import example.repository.scalike.CargosPerContainerRepositoryImpl

object Main {

  def main(args: Array[String]): Unit = ...

  def initActorSystem(port: Int):ActorSystem[_] = ...

  def initProjection(system: ActorSystem[_])
      : Unit  = {
    ShardedDaemonProcess(system).init(
      name = "cargos-per-container-projection",
      3,                                                    ❶
      index =>
        ProjectionBehavior(                                 ❷
          CargosPerContainerProjection.createProjectionFor(
            system,
            new CargosPerContainerRepositoryImpl(),
            index)),
      ShardedDaemonProcessSettings(system),                 ❸
      Some(ProjectionBehavior.Stop))                        ❹
  }
}
```

❶ Number of instances of the ProjectionBehavior

❷ Behavior factory

❸ Settings

❹ Stops when rebalanced or passivated and closes the connection to the database

This `ShardedDaemonProcess` is essentially the same one you saw earlier. It has a name, the number of behaviors to spawn, and the behavior, along with two other attributes you haven't seen before:

- `settings`—`ShardedDaemonProcessSettings`
- `stopMessage`—`Optional[T]`

`ShardedDaemonProcessSettings(system)` exists so you can read from your configuration if you want to configure `akka.cluster.sharded-daemon-process .keep-alive-`