```
      ActorSystem[Nothing](Behaviors.empty,"containersprojection",config)
  }

  def initProjection (system: ActorSystem[_]): Unit  = ...
}
```

❶ Sets a random port
❷ Sets a port passed as a parameter
❸ Initializes the connection to the database
❹ Initializes the projection with ShardedDaemonProcess
❺ Graceful shutdown
❻ Creates an ActorSystem with a port and default config

10.4 Projections in action

You can create the journal with the chapter09b project and the projection with chapter10c. First you create persistence entity entries. To do this, create the database and the necessary persistence entity tables to store the journal, tags, and snapshots. Then start the cluster and create persistence entities using the console. Here are the steps to follow:

1. Start the Postgres database with the script in the project persistence docker-compose.yml by running the following from the command line in the root directory of the chapter09b project:

```
$ docker compose up
```

2. Create the `event_journal`, `event_tag`, and `snapshot` tables with the projections/persistence_create_tables.sql script by executing the following from the command line in the root directory of the chapter09b project:

```
$ psql -h 127.0.0.1 -d containers -U containers \
      -f persistence_create_tables.sql
$ Password for user containers:          ❶
```

❶ Enter containers

3. Launch one node of the persistence entity application from chapter 9 in the sbt console by running the following from the command line in the root of the Git repository:

```
$ sbt chapter09b/run
```

4. In this console, add three entries of the type `[containerId, cargoId, cargo- Kind, cargoSize]` by pressing Enter before and after the following values:

```
 9 456 sack 22
 9 456 sack 22
11 499 barrel 120
```

This will give you the data listed in table 10.4 in the journal.

Table 10.4 Events from table `event_journal`