Table 10.5 `cargos_per_container` for projections

containerId	cargo
11	1
9	2

Table 10.6 `akka_projection_offset_store` for projections

projection_name	projection_key	current_offset	manifest	mergeable	last_upda
CargosPerContainerProjection	container-tag-0	1	SEQ	FALSE	16222995333
CargosPerContainerProjection	container-tag-2	2	SEQ	FALSE	16222995332

From now on, any new event added to the journal of the `SPContainer` will be picked up for the projection, and the tables `cargos_per_container` and `current _offset` will be updated accordingly.

This example doesn't take full advantage of the `ShardedDaemonProcess` running multiple processes on different nodes. You can easily start another node by opening another sbt console in the root of the Git repository and running `main` with a different port:

```
$ sbt "chapter10c/runMain example.projection.Main 25526"
```

You will quickly find that this new node takes over one of the three tags of the other node, balancing a shard and its projection onto this new node. In the log of the new node is an entry like the following:

```
[INFO] [akka.projection.ProjectionBehavior$] [] [containersprojection-
➥akka.actor.default-dispatcher-5] - Starting projection
➥[ProjectionId(CargosPerContainerProjection, container-tag-0)]
```

The next chapter is about ports. So far, you've connected to an Akka application through the console, but that is just for convenience. In the real world, you usually connect to an Akka application through endpoints like HTTP and gRPC. Chapter 11 examines how to create a server with these endpoints.

Summary

- Akka Streams abstract from producers, transformations, and consumers as data streams, creating pure functions that are composable.
- Akka Streams are useful in their own right, but they also form the basis for other modules such as Akka Persistence Query and Akka Projections.
- Akka Persistence Query gives you an infinite stream of persistence IDs, events by tag, or events by persistence ID. But normally, you don't use the persistence query on its own. To consume the journal, you typically use Akka projections.