Listing 11.1 Basic server with a GET method

```
import akka.actor.typed.ActorSystem
import akka.actor.typed.scaladsl.Behaviors
import akka.http.scaladsl.Http
import akka.http.scaladsl.model._
import akka.http.scaladsl.server.Directives._
import scala.io.StdIn

object HttpServer {

  def main(args: Array[String]): Unit = {

    implicit val system = ActorSystem(Behaviors.empty, "simple-api")     ❶

    implicit val executionContext = system.executionContext              ❷

    val route: Route =
      path("ping") {                                                     ❸
        get {                                                            ❹
          complete("pong")                                               ❺
        }
      }

    val bindingFuture: Future[ServerBinding] =
      Http().newServerAt("localhost", 8080).bind(route)                  ❻

    println(s"server at localhost:8080 \nPress RETURN to stop")
    StdIn.readLine()                                                     ❼
    bindingFuture                                                        ❼
      .flatMap(_.unbind())                                               ❼
      .onComplete(_ => system.terminate())                               ❼
  }
}
```

❶ ActorSystem to run the server

❷ Thread pool of the ActorSystem to run bindingFuture

❸ Server route path

❹ HTTP method

❺ Returns the value to the client

❻ Starts the server with a route

❼ Listens to Enter at the command line to trigger a system shutdown