This plugin uses Akka HTTP, Akka Streams, `akka-discovery`, and `akka-http2-support`. Add the first three to your build.sbt to avoid conflicts with transitive dependencies and the last one to enable HTTP/2:

```
val AkkaVersion = "2.6.20"
val AkkaHttpVersion = "10.2.9"

libraryDependencies ++= Seq(
    "com.typesafe.akka" %% "akka-http" % AkkaHttpVersion,
    "com.typesafe.akka" %% "akka-stream" % AkkaVersion,
    "com.typesafe.akka" %% "akka-discovery" % AkkaVersion,
    "com.typesafe.akka" %% "akka-http2-support" % AkkaHttpVersion)
```

You enable the plugin in the build.sbt. In the Git repository in the project, gRPC is set as follows:

```
    lazy val chapter11b = project
    .in(file("chapter11b"))
    .enablePlugins(AkkaGrpcPlugin)    ❶
    .settings(
      scalaVersion := ScalaVersion,
      libraryDependencies ++= Seq(
        "com.typesafe.akka" %% "akka-actor-typed" % AkkaVersion,
        "com.typesafe.akka" %% "akka-stream" % AkkaVersion,
        ...                           ❷
      ))
```

❶ Enables the plugin in the gRPC project

❷ The rest of the libraries

After all this preparation, you can create the .proto file to generate a service like the one in section 11.1.6, where you can add cargo to the container and query the list. But first, let’s create a dummy service that responds to adding cargo.

You can use an RPC called `AddCargo` to create a .proto file that defines the request message `Cargo`, the response message