Listing 12.6 Remaining command handler methods

```
object Market{
  ...

  def open(
      state: State,
      command: Open): ReplyEffect[Opened, State] = {              ❶
    Effect
      .persist(Opened(state.status.marketId))
      .thenReply(command.replyTo)(_ => Accepted)
  }

  def update(
      state: State,
      command: Update): ReplyEffect[Updated, State] = {           ❶
    val updated = Updated(state.status.marketId, command.odds)
    Effect
      .persist(updated)
      .thenReply(command.replyTo)(_ => Accepted)
  }

  def close(
      state: State,
      command: Close): ReplyEffect[Closed, State] = {             ❶
    val closed = Closed(
      state.status.marketId,
      OffsetDateTime.now(ZoneId.of("UTC")))
    Effect
      .persist(closed)
      .thenReply(command.replyTo)(_ => Accepted)
  }

  def cancel(
      state: State,
      command: Cancel): ReplyEffect[Cancelled, State] = {         ❶
    val cancelled = Cancelled(state.status.marketId, command.reason)
    Effect
      .persist(cancelled)
      .thenReply(command.replyTo)(_ => Accepted)
  }

  def tell(
      state: State,
      command: GetState): ReplyEffect[Event, State] = {           ❷
    Effect.none.thenReply(command.replyTo)(_ => CurrentState(state))
  }

  def invalid(
```