```
      implicit val ec: ExecutionContext = system.executionContext

      AkkaManagement(system).start()                                    ❷
      ClusterBootstrap(system).start()
      ...                                                               ❸
      BetServiceServer.init(system, sharding, ec)                       ❹
      MarketServiceServer.init(system, sharding, ec)                    ❹
      WalletServiceServer.init(system, sharding, ec)                    ❹
      ...                                                               ❸
    } catch {
      case NonFatal(ex) =>
        log.error(
          s"Terminating Betting App. Reason [${ex.getMessage}]")
        system.terminate
    }
  }
}
```

❶ Sharding extension to be passed around, allowing entities such as Bet, Market, and Wallet and the Bet and Market projections to register with it

❷ HTTP server to provide endpoints for cluster bootstrapping

❸ Projection-related functionality (ignored for now)

❹ Starts the HTTP servers, allowing communication with the Bet, Market, and Wallet entities

You can see on the repository how the server endpoints can be started: bet, market, and wallet. All of them follow the same structure. The ports for each service are as follows:

```
services {
  bet.port = 9000
  wallet.port = 9001
  market.port = 9002
}
```

You can run this locally by executing the betting-house project with the local configuration, following the instructions in betting-house/README.md.

If the cluster is running, you can query the market service with `grpcurl localhost:9002 -list` to get the list of available