❹ Names the service

❺ Discovery by fixed IPs

Now you can create the application and start both modules: `ClusterBootstrap` and `AkkaManagement`. This way, the application exposes the nodes, and the bootstrap can create the cluster. The following listing shows a minimal application.

Listing 13.2 App to form the cluster

```
import akka.management.scaladsl.AkkaManagement
import akka.management.cluster.bootstrap.ClusterBootstrap
import akka.actor.typed.ActorSystem
import akka.actor.typed.scaladsl.Behaviors
import com.typesafe.config.ConfigFactory

object App {

  def main(args: Array[String]): Unit = {
    val i = args(0)                                    ❶

    val config = ConfigFactory
      .parseString(s"""                                ❷
        akka.remote.artery.canonical.hostname = "127.0.0.$i"
        akka.management.http.hostname = "127.0.0.$i"
        """)
      .withFallback(ConfigFactory.load())              ❸

    val system =                                       ❹
      ActorSystem[Nothing](
        Behaviors.empty,
        "testing-bootstrap",
        config)

    AkkaManagement(system).start()                     ❺
    ClusterBootstrap(system).start()                   ❻
  }
}
```

❶ Parameter to fix the IP of the node's configuration

❷ Fixes the IP of the node's configuration

❸ Loads the default: that is, application.conf

❹ Starts the system with no functionality but the basic cluster