```
➥nodes []                                                              ❼
Discovered [2] contact points, confirmed [1], which is less than the    ❼
➥required [2],retrying                                                 ❼
```

❶ Sets Cluster Bootstrap as joining mechanism

❷ Akka Management starts

❸ Accepts the discovery method from application.conf

❹ Sets the lowest address as the initial seed-node

❺ Looks up nodes belonging to testing-bootstrap ActorSystem

❻ Retrieves the possible seed nodes

❼ Loops, retrieving an empty list of seed nodes and failing to reach the required number of contact points

In the first line, the node looks for the list of seed nodes (`akka.cluster.seed-nodes`), and they are not present. Since the node doesn't find them, it switches to Cluster Bootstrap. `akka.cluster.seed-nodes` takes precedence over bootstrap configuration. You must be careful not to mix the two and to use only one method in your configuration.

Then the node starts the Akka Management Service and loads the `discovery` method specified in application.conf. By default, the service looks for the member with the lowest address to set it as the starting node. Eventually, the service finds the IPs of the members in the configuration, but it can't retrieve them all. It only finds the node you just started, and since it doesn't reach the minimum number of contact points, the cluster can't be formed; therefore, this node can't be set as the seed node. Hence the "empty list of seed nodes" message in the output. From this point on, the output is in a loop with the last two messages: empty seed nodes and fewer contact points than required.

Now you can start node 2 with this command: