```
sbt "chapter13a/runMain example.clustering2.App 2"
```

Look at the output of node 1, which shows the following:

```
Node [akka://testing-bootstrap@127.0.0.1:25520] is JOINING itself (with
➥roles [dc-default], version [0.0.0]) and forming new cluster              ❶
Node [akka://testing-bootstrap@127.0.0.1:25520] is the new leader among
➥reachable nodes (more leaders may exist)                                  ❷
Leader is moving node [akka://testing-bootstrap@127.0.0.1:25520] to [Up]    ❸
Bootstrap request from 127.0.0.1:50504: Contact Point returning 1 seed-
➥nodes [akka://testing-bootstrap@127.0.0.1:25520]                          ❹
```

❶ Gets to the Joining state

❷ Sets itself as leader

❸ Gets to the Up state

❹ Returns itself as the only seed node

Once the number of contact points matches the required number, the node with the lowest IP address (172.0.0.1) starts the cluster. It switches from `Joining` to `Up` and makes itself available as a seed node for all other nodes via Akka Management. Node 1 then receives the request from node 2 to join the cluster, as you can see in its logs:

```
Received InitJoin message from [Actor[akka://testing-
➥bootstrap@127.0.0.2:25520/system/...]] to [akka://testing-
➥bootstrap@127.0.0.1:25520]                                                ❶
Sending InitJoinAck message from node [akka://testing-
➥bootstrap@127.0.0.1:25520] to [Actor[akka://testing-
➥bootstrap@127.0.0.2:25520/system/...] (version [2.6.20])                  ❷
Node [akka://testing-bootstrap@127.0.0.2:25520] is JOINING, roles [dc-
➥default], version [0.0.0]                                                 ❸
Node added [UniqueAddress(akka://testing-
➥bootstrap@127.0.0.2:25520,8717661260050472844)]                           ❹
Leader is moving node [akka://testing-bootstrap@127.0.0.2:25520] to [Up]    ❺
```

❶ Initial request to join

❷ Sends back ack

❸ Node 2 advertises its Joining state