```
addSbtPlugin("com.typesafe.sbt" % "sbt-native-packager" % "1.9.11")
```

Before you create the Docker image, you need more dependencies in addition to the previous `akka-management-cluster-bootstrap`. To use the Kubernetes API server to find the nodes, it needs the `akka-discovery-kubernetes-api` module and `akka-management-cluster-http` to publish the `/health` and `/ready` endpoints. Kubernetes needs these to verify that the service is alive and ready to take work:

```
val AkkaManagementVersion = "1.1.4"

  "com.lightbend.akka.management" %% "akka-management-cluster-http" %
  ➥AkkaManagementVersion,
  "com.lightbend.akka.discovery" %% "akka-discovery-kubernetes-api" %
  ➥AkkaManagementVersion
```

With the plugin and these two libraries in place, you can create the Docker image and deploy it as a cluster.

NOTE The source code for this example is available at www.manning.com/books/akka-in-action-second-edition or https://github.com/franciscolopez sancho/akka-topics/tree/main/chapter13b. You can find the contents of any snippet or listing in the .scala file with the same name as the class, object, or trait.

13.2.1 Creating the Docker image

To create the container, add the following to the build.sbt file:

```
version := "0.1.0-SNAPSHOT"                    ❶
enablePlugins(JavaAppPackaging, DockerPlugin)  ❷
```