```
role.rbac.authorization.k8s.io/pod-reader created
rolebinding.rbac.authorization.k8s.io/read-pods created

$ kubectl -n akka-cluster apply -f deployment.yml              ❹
deployment.apps/testing-bootstrap13b created
```

❶ Creates the namespace akka-cluster

❷ Creates the SA in the namespace akka-cluster

❸ Creates the role binding to the SA akka-cluster in the namespace akka-cluster

❹ Deploys the app as a cluster in the namespace akka-cluster

Once this is done, your Akka cluster is in place. You can check by typing `kubectl -n akka-cluster get po` like this:

```
$ kubectl -n akka-cluster get po

NAME                                    READY   STATUS    RESTARTS   AGE
testing-bootstrap13b-565d68bd5b-ggljg   1/1     Running   0          47s   ❶
testing-bootstrap13b-565d68bd5b-s5vz2   1/1     Running   0          47s   ❶
testing-bootstrap13b-565d68bd5b-wls2d   1/1     Running   0          47s   ❶
```

❶ All nodes are alive and ready after 47 seconds.

In the logs of the `testing-bootstrap13b-565d68bd5b-ggljg` node shown in the following snippet, the cluster is formed:

```
$ kubectl -n akka-cluster logs testing-bootstrap13b-565d68bd5b-ggljg


Cluster Node [akka://testing-bootstrap13b@172.17.0.3:25520] - is the new
➥leader among reachable nodes (more leaders may exist)
...
Leader is moving node [akka://testing-bootstrap13b@172.17.0.3:25520] to [Up]❶
...
Leader is moving node [akka://testing-bootstrap13b@172.17.0.4:25520] to [Up]❷
...                                                                          ❷
Leader is moving node [akka://testing-bootstrap13b@172.17.0.5:25520] to [Up]❷
```

❶ Moves itself to the Up state

❷ Moves the other nodes to the Up state