- `Lease-majority`—Combines `keep-majority` with distributed locking. In partitioning, each cluster attempts to obtain the lock, and the cluster with fewer nodes is penalized with a delay. Only the cluster that acquires the lock stays alive. There is only one implementation in Akka (http://mng.bz/eJWZ), and it is built on a Kubernetes lease (https://kubernetes.io/docs/reference/kubernetes-api/cluster-resources/lease-v1/):
    - *Recommended for*—This is the safest option but incurs higher operational costs as various Kubernetes resources need to be created.
    - *Options*—You can filter the number by role, set the delay for the cluster with fewer nodes, and set the duration of the lease after which the lock is released.
    - *Corner case*—If the node acquiring the lease crashes before notifying its cluster, the lease cannot be reached by any other node, and all clusters are terminated. In either case, it depends on the Kubernetes lease working properly. If the lease cannot be acquired, all clusters are terminated.
- `Static-quorum`—Any cluster with fewer nodes than specified in the configuration is terminated:
    - *Recommended*—If there is a fixed number of nodes in the cluster.
    - *Options*—You can filter the number by role.
    - *Corner cases*—If the cluster splits into three instead of two and no cluster meets the quorum, all stop. If the cluster splits into two and no node is added to the one that stays alive, any further splits will stop all clusters.