```
        new StringDeserializer(),
        new StringDeserializer())
        .withBootstrapServers("127.0.0.1:9092")
        .withGroupId("group01")

    Consumer
      .plainSource(consumerSettings, Subscriptions.topics("test"))
      .map { msg: ConsumerRecord[String, String] =>
        println(
           s"key = ${msg.key},
           value = ${msg.value},
           offset = ${msg.offset}")
      }
      .runWith(Sink.ignore)                                          ❹


    StdIn.readLine("Consumer started \n Press Enter to stop")
    system.terminate()
  }
}
```

❶ Implicit ActorSystem to provide a materializer to run the stream

❷ Loads the Kafka default configuration from the Alpakka reference.conf file

❸ Alpakka consumer settings

❹ Consumes and discards the elements

14.1.1 Consuming from Kafka in action

You can run the example from your Git repository using the docker-compose.yml on the base of the Alpakka project to start a Kafka server. You need to run `docker compose up` from the base of the chapter 14 folder in the command line. After a few seconds, Kafka should be running. By default, this Docker compose file creates six topics: `test`, `test2`, ..., `test6`.

On another command line, start the `ConsumerPlainSource` application by typing `sbt chapter14/run` and selecting option 1. When this application starts, it outputs information about the Kafka consumer's configuration, Kafka version, and more: