```
[INFO] [...] - [Consumer clientId=consumer-group01-1, groupId=group01]
➥Subscribed to topic(s): test                                          ❶

[INFO] [...] - [Consumer clientId=consumer-group01-1, groupId=group01]
➥Finished assignment for group at generation 1: {consumer-group01-1-
➥a37940c9-2767-4983-b2b7-005340617066=Assignment(partitions=[test-0])}  ❷

[INFO] [...] - [Consumer clientId=consumer-group01-1, groupId=group01]
➥Found no committed offset for partition test-0                        ❸

[INFO] [...] - [Consumer clientId=consumer-group01-1, groupId=group01]
➥Resetting offset for partition test-0 to position
➥FetchPosition{offset=0, ...}                                          ❹
```

❶ Subscription to the topic test

❷ Assigns one partition to your group's consumer

❸ No offset found for this group

❹ Resets the offset to position 0 for this group

Once the application is running, you can send messages with `kcat` by starting a producer with the following command on another command line:

```
$ kcat -P -b localhost:9092 -t test
```

`-P` stands for *producer*. Now, each line you type sends a message to the test topic. If you enter `hello` and `hi`, you see the following in the `ConsumerPlainSource` output (partially formatted to make it easier to read):

```
key = null, value = hello, offset = 0
key = null, value = hi, offset = 1
```

The two lines sent through `kcat` are converted into records—more precisely, into two `org.apache.kafka.clients.consumer.ConsumerRe`