```
        "surname" -> ByteString("Pleasence"),
        "age" -> ByteString("19")))
  }
  ...
}
```

❶ Converts to Seq[Map[String, ByteString]] with headers

The method .`withHeaders` not only adds the headers but also returns a map that you can use later.

Strings as values instead of ByteString

A method similar to `.withHeaders` is `CsvToMap.toMapAsStrings()`, which returns a `Seq[Map[String,String]]` as a result instead of a `Seq[Map[String, ByteString]]`. With `String` values as results, you have a much richer API thanks to `StringsOps`.

In Scala, any `String` gets wrapped in a `StringOps` through `Predef` by `.augmentString` (see http://mng.bz/jmMV). Both `.toMap` and `.withHeaders` have `asString` flavors, which are `.toMapAsString` and `.withHeadersAsString`, respectively.

14.4.2 Reading and writing with FileIO

To read a CSV file or any other file, you can use `FileIO`. First, import the following dependencies in your build.sbt file:

```
val AkkaStreamAlpakka = "4.0.0"
val AkkaVersion = "2.6.20"

libraryDependencies ++= Seq(
  "com.lightbend.akka" %% "akka-stream-alpakka-file" % AkkaStreamAlpakka,
  "com.typesafe.akka" %% "akka-stream" % AkkaVersion
)
```