```
      repository: BetRepository): Unit = {
    ShardedDaemonProcess(system).init(
      name = "bet-projection",
      Bet.tags.size,                                          ❶
      index =>
        ProjectionBehavior(
          BetProjection
            .createProjection(system, repository, index)),   ❷
      ShardedDaemonProcessSettings(system),                   ❸
      Some(ProjectionBehavior.Stop))                          ❹
  }
  ...
}
```

❶ Tags used in the Bet entity to tag the events

❷ Creates as many projections as Bet tags

❸ Loads the default settings: akka.cluster.sharded-daemon-process from the akka-cluster-sharding-typed library

❹ Message sent to the behavior to stop it in case of a rebalance or shutdown

15.1.3 The betting-house entry point

Finally, we have reached the entry point of the betting-house application: `Main`, with everything you've learned since chapter 12. It includes sharding, the cluster bootstrap, management, adding the JDBC session in scope, the services as ports to the actors, and the projections.

Listing 15.7 Entry point of the betting-house application

```
object Main {

  val log = LoggerFactory.getLogger(Main + "")

  def main(args: Array[String]): Unit = {
    implicit val system =
      ActorSystem[Nothing](Behaviors.empty, "betting-house")
    try {
      val sharding = ClusterSharding(system)                  ❶
      implicit val ec: ExecutionContext = system.executionContext
```