```
      AkkaManagement(system).start()                                  ❷
      ClusterBootstrap(system).start()                                ❸
      ScalikeJdbcSetup.init(system)                                   ❹

      BetServiceServer.init(system, sharding, ec)                     ❺
      MarketServiceServer.init(system, sharding, ec)                  ❺
      WalletServiceServer.init(system, sharding, ec)                  ❺

      val betRepository = new BetRepositoryImpl()                     ❻
      BetProjectionServer.init(betRepository)                         ❼
      BetProjection.init(system, betRepository)                       ❽
      MarketProjection.init(system)                                   ❾
    } catch {
      case NonFatal(ex) =>
        log.error(
          s"Terminating Betting App. Reason [${ex.getMessage}]")
        system.terminate
    }

  }
}
```

❶ Sharding extension to be passed around, allowing entities to register, such as the bet, market, and wallet entities and the bet and market projections

❷ HTTP server to provide management endpoints

❸ Mechanism to auto-discover nodes to form a cluster

❹ Connection to the database to be used implicitly by the projections

❺ Starts HTTP servers, allowing communication with the bet, market, and wallet entities

❻ Repository to be used by the bet projection

❼ Server to expose the bet projection query

❽ Initializes the bet projection

❾ Initializes the market projection

With this, you have an application you can deploy and for which you need the configuration.

15.2 Configuration