```
  bootstrap.servers = "127.0.0.1:9092"              ❹
}
akka.kafka.producer {
  kafka-clients = ${kafka-connection-settings}      ❺
}
```

❶ Host and ports for each service

❷ Sharding for the entities and the projections

❸ Projection topic name

❹ The only difference, in this listing, between the local and Kubernetes configurations

❺ Configuration for org.apache.kafka .clients.producer.ProducerConfig

It is worth remembering that sharding is applied not only to the entities but also to the projections that use `ShardedDaemonProcess` with the tags as partition keys. On the Kubernetes configuration, `bootstrap.servers` has `my-cluster-kafka-bootstrap` instead of the fixed host. This name resolves to a service in Kubernetes that proxies the connection to the brokers. For more information, see section 15.3.2.

Note that `akka.kafka.producer` refers to the previously defined `kafka-connection-settings`. You can add any additional configuration that you want to apply to `org.apache.kafka.clients.producer.ProducerConfig`. The producer settings use this in the market projection, shown again in the following snippet:

```
object MarketProjection {
  ...

  def createProducer(
      system: ActorSystem[_]): SendProducer[String, Array[Byte]] = {

    val producerSettings =
      ProducerSettings(          ❶
        system,
        new StringSerializer,
```