The application.conf file you saw earlier had the following value for the JDBC connection:

```
url = "jdbc:postgresql://postgres-betting-db:5432/betting"
```

`postgres-betting-db` is the database's host name and is set in the two .yml files from the previous snippet so that when the application is deployed, it knows where to look.

Once the database is running, create the necessary tables in the database to store journal, tags, and events. You can connect to the database with a Kubernetes port-forward (http://mng.bz/81VW) and then run the SQL scripts as shown in the following snippets. Port forwarding redirects all requests from your local port 5432 to the same port in the Postgres pod:

```
$ kubectl get pod -n akka-cluster                                    ❶
NAME                                    READY   STATUS    RESTARTS   AGE
postgres-containers-db-85b9cf78b6-rw95h   1/1     Running   0          47s ❶

$ kubectl port-forward \                                             ❷
       pods/postgres-containers-db-85b9cf78b6-rw95h 5432:5432  \     ❷
       -n akka-cluster                                               ❷
```

❶ Finds the database pod

❷ Port-forwards directly to the database pod

Once port forwarding is set up, you can open another terminal and apply the SQL in the scripts from betting-house/common-deployment as follows:

```
$ psql -h 127.0.0.1 -d betting  -U betting -f bet-projection.sql      ❶
$ psql -h 127.0.0.1 -d betting  -U betting -f akka-persistence.sql    ❶
$ psql -h 127.0.0.1 -d betting  -U betting -f akka-projection.sql     ❶
```