request, use `RequestBuilding.Get`, as follows:

```
class CPUNonBoundedSpec ... {
  ...
     ...
     Http().singleRequest(
        Get("http://localhost:8080/validate?quantity=" + each)))
   ...
}
```

All this belongs to the Akka HTTP client side. You can deserialize the response using `Unmarshal`, for which you need an implicit `jsonFormatX`. The service response is the `Validated(accepted: Boolean)` class, so you need a `jsonFormat1`:

```
import akka.http.scaladsl.marshallers.sprayjson.SprayJsonSupport._
import spray.json.DefaultJsonProtocol._

class CPUNonBoundedSpec ... {
  ...

  implicit val validatedFormat
      : RootJsonFormat[HttpServer.Validated] = jsonFormat1(HttpServer.Validated)
  ...
   Unmarshal(each).to[HttpServer.Validated])
  ...
}
```

You can see this tested in the following listing.

Listing 16.2 Calling an HTTP service from an Akka stream

```
import akka.http.scaladsl.client.RequestBuilding.Get
import akka.http.scaladsl.Http
import akka.http.scaladsl.unmarshalling.Unmarshal
import akka.http.scaladsl.marshallers.sprayjson.SprayJsonSupport._
import spray.json.DefaultJsonProtocol._

import example.streams.two.HttpServer
```