```
Location(3.0,-3.701101)
Location(4.0,-3.701101)
[11:09:22,525] [WARN] [akka.stream.scaladsl.RestartWithBackoffSource] []
➥[SampleSpec-akka.actor.default-dispatcher-3] - Restarting stream due
➥to failure [1]: io.grpc.StatusRuntimeException: UNAVAILABLE: io exception
      ...
[11:09:23,679] [WARN] [akka.stream.scaladsl.RestartWithBackoffSource] []
➥[SampleSpec-akka.actor.default-dispatcher-3] - Restarting stream due
➥to failure [2]: io.grpc.StatusRuntimeException: UNAVAILABLE: io exception
      ...
```

You can see the first four elements of the stream being consumed and then the `RestartSource`—unable to continue consuming from the gRPC service—attempting to restart the stream but failing due to an error `[1]`, where `[1]` stands for the first restart attempt (the listing shows two). There will be more of these in the log, each a second later than the previous one, with a maximum of 3 seconds difference: 1 second between `[1]` and `[2]`, 2 seconds between `[2]` and `[3]`, and 3 seconds from then on, as specified in the restart settings:

```
class LocatorServiceSpec ... {
  ...

      val restartSettings = RestartSettings(
        minBackoff = 1.seconds,
        maxBackoff = 3.seconds,
        randomFactor = 0.2).withMaxRestarts(30, 3.minutes)
  ...
}
```

NOTE You may have noticed that the time difference between two consecutive retries is not exactly 1 or 2 seconds. This is because of the `randomFactor`.

After a few seconds, you can restart the service with the following command: