storage, and cookies. The Mozilla Developer Network has an excellent article on the SOP at https://developer.mozilla.org/en-US/docs/Web/Security/Same-origin_policy.
Broadly speaking, the SOP will allow many requests to be sent from one origin to another, but it will stop the initiating origin from being able to read the response. For example, if a JavaScript loaded from https://www.alice.com makes a POST request to http://bob.net, then the request will be allowed (subject to the conditions described below), but the script will not be able to read the response or even see if it was successful. Embedding a resource using a HTML tag such as `<img>`, `<video>`, or `<script>` is generally allowed, and in some cases, this can reveal some information about the cross-origin response to a script, such as whether the resource exists or its size.
Only certain HTTP requests are permitted cross-origin by default, and other requests will be blocked completely. Allowed requests must be either a GET, POST, or HEAD request and can contain only a small number of allowed headers on the request, such as Accept and Accept-Language headers for content and language negotiation. A Content-Type header is allowed, but only three simple values are allowed:

- application/x-www-form-urlencoded
- multipart/form-data
- text/plain

These are the same three content types that can be produced by an HTML form element. Any deviation from these rules will result in the request being blocked. Cross-origin resource sharing (CORS) can be used to relax these restrictions, as you'll learn in chapter 5.

To instruct Spark to serve your HTML and JavaScript files, you add a `staticFiles` directive to the main method where you have configured the API routes. Open Main.java in your text editor and add the following line to the main method. It must come before any other route definitions, so put it right at the start of the main method as the very first line.

```
Spark.staticFiles.location("/public");
```

This instructs Spark to serve any files that it finds in the src/main/java/resources/public folder.