remain `null` in the request and access will be denied for any request that requires authentication. This means that the API can continue to support either method of authentication, providing flexibility for clients.

Restart the API and you can now try out making requests using a session cookie instead of using HTTP Basic on every request. First, create a test user as before:

```
$ curl -H 'Content-Type: application/json' \
  -d '{"username":"test","password":"password"}' \
  https://localhost:4567/users
{"username":"test"}
```

Next, call the `/sessions` endpoint to login, passing the username and password as HTTP Basic authentication credentials. You can use the `-c` option to curl to save any cookies on the response to a file (known as a cookie jar):

```
$ curl -i -c /tmp/cookies -u test:password \    #A
  -H 'Content-Type: application/json' \
  -X POST https://localhost:4567/sessions
HTTP/1.1 201 Created
Date: Sun, 19 May 2019 19:15:33 GMT
Set-Cookie:
[CA]JSESSIONID=node0l2q3fc024gw8wq4wp961y5rk0.node0;
   [CA]Path=/;Secure;HttpOnly    #B
Expires: Thu, 01 Jan 1970 00:00:00 GMT
Content-Type: application/json
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Cache-Control: private, max-age=0
Server:
Transfer-Encoding: chunked
```