```
$ curl -H 'Content-Type: application/json' \
  -d '{"username":"test","password":"password"}' \
  https://localhost:4567/users
{"username":"test"}
```

You can then login to create a new session. Notice how the token returned in the JSON is now different to the session ID in the cookie.

```
$ curl -i -c /tmp/cookies -u test:password \
  -H 'Content-Type: application/json' \
  -X POST https://localhost:4567/sessions
HTTP/1.1 201 Created
Date: Mon, 20 May 2019 16:07:42 GMT
Set-Cookie:
JSESSIONID=node01n8sqv9to4rpk11gp105zdmrhd0.node0;Path=/;Secu
re;HttpOnly    #A
…
{"token":"gB7CiKkxx0FFsR4lhV9hsvA1nyT7Nw5YkJw_ysMm6ic"}    #A
```

#A The session ID in the cookie is different to the hashed one in the JSON body.

If you send the correct X-CSRF-Token header, then requests succeed as expected:

```
$ curl -i -b /tmp/cookies -H 'Content-Type: application/json'
\
  -H 'X-CSRF-Token:
gB7CiKkxx0FFsR4lhV9hsvA1nyT7Nw5YkJw_ysMm6ic' \    #A
  -d '{"name":"test space","owner":"test"}' \
  https://localhost:4567/spaces
HTTP/1.1 201 Created
```