```
var keyStore = KeyStore.getInstance("PKCS12");    #B
keyStore.load(new FileInputStream("keystore.p12"),    #B
        keyPassword);    #B

var macKey = keyStore.getKey("hmac-key", keyPassword);    #C

TokenStore tokenStore = new DatabaseTokenStore(database);
#D
tokenStore = new HmacTokenStore(tokenStore, macKey);    #D
var tokenController = new TokenController(tokenStore);
```

#A Load the keystore password from a system property.
#B Load the keystore, unlocking it with the password.
#C Get the HMAC key from the keystore, using the password again.
#D Create the HmacTokenStore, passing in the DatabaseTokenStore and the HMAC key.

TRYING IT OUT

Restart the API, adding `-Dkeystore.password=changeit` to the command line arguments, and you can see the update token format when you authenticate:

```
$ curl -H 'Content-Type: application/json' \    #A
  -d '{"username":"test","password":"password"}' \    #A
  https://localhost:4567/users    #A
{"username":"test"}
$ curl -H 'Content-Type: application/json' -u test:password
\    #B
  -X POST https://localhost:4567/sessions    #B
{"token":"OrosINwKcJs93WcujdzqGxK-d9s
[CA].wOaaXO4_yP4qtPmkOgphFob1HGB5X-bi0PNApBOa5nU"}
```