already seen two standard JWT claims, because you used them in the implementation of the `JsonTokenStore`:

- The `exp` claim indicates the expiry time of a JWT in UNIX time, which is the number of seconds since midnight on January 1st, 1970 in UTC.
- The `sub` claim identifies the subject of the token: the user. Other claims in the token are generally making claims about this subject.

JWT defines a handful of other claims too, which are listed in table 6.1. To save space, each claim is represented with a 3-letter JSON object property.

Table 6.1 Standard JWT claims

Claim	Name	Purpose
`iss`	Issuer	Indicates who created the JWT. This is a single string and often the URI of the authentication service.
`aud`	Audience	Indicates who the JWT is for. An array of strings identifying the intended recipients of the JWT. If there is only a single value, then it can be a simple string value rather than an array. The recipient of a JWT must check that its identifier appears in the audience, otherwise it should reject the JWT. Typically, this is a set of URIs for APIs where the token can be used.
`iat`	Issued-At	The UNIX time at which the JWT was created.
`nbf`	Not-Before	The JWT should be rejected if used before this time.
`exp`	Expiry	The UNIX time at which the JWT expires and should be rejected by recipients.
`sub`	Subject	The identity of the subject of the JWT. A string. Usually a username or other unique identifier.
`jti`	JWT ID	A unique ID for the JWT, which can be used to detect replay.

Of these claims, only the issuer, issued-at, and subject claims express a positive statement. The remaining fields all describe constraints on how the token can be used rather