from https://connect2id.com/products/nimbus-jose-jwt, which is a well-maintained open-source (Apache 2.0 licensed) Java JOSE library. Open the pom.xml file in the Natter project root folder and add the following dependency to the dependencies section to load the Nimbus library:

```
    <dependency>
      <groupId>com.nimbusds</groupId>
      <artifactId>nimbus-jose-jwt</artifactId>
      <version>8.3</version>
    </dependency>
```

Listing 6.3 shows how to use the library to generate a signed JWT. The code is generic and can be used with any JWS algorithm, but for now you'll use the `HS256` algorithm, which uses HMAC-SHA-256, just like the existing `HmacTokenStore`. The Nimbus library requires a `JWSSigner` object for generating signatures, and a `JWSVerifier` for verifying them. These objects can often be used with several algorithms, so you should also pass in the specific algorithm to use as a separate `JWSAlgorithm` object. Finally, you should also pass in a value to use as the audience for the generated JWTs. This should usually be the base URI of the API server, such as `https://localhost:4567`. By setting and verifying the audience claim you ensure that a JWT can't be used to access a different API, even if they happen to use the same cryptographic key. To produce the JWT you first build the claims set, setting the `sub` claim to the username, and the `exp` claim to the token expiry time, and the `aud` claim to the audience value you got from the constructor. You can then set any other attributes of the token as a custom claim,