You can now restart the API and use the JWT to create a new social space:

```
$ curl -H 'Content-Type: application/json' \
  -H 'Authorization: Bearer
eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJ0ZXN
[CA]0IiwiYXVkIjoiaHR0cHM6XC9cL2xvY2FsaG9zdDo0NTY3IiwiZXhwIjox
NTc
[CA]3MDEyMzA3LCJhdHRycyI6e319.JKJnoNdHEBzc8igkzV7CAYfDRJvE7oB
2md
[CA]6qcNgc_yM' -d '{"owner":"test","name":"test space"}' \
  https://localhost:4567/spaces -i
HTTP/1.1 201 Created
Date: Sun, 22 Dec 2019 10:49:21 GMT
Location: /spaces/1
Content-Type: application/json;charset=utf-8
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-XSS-Protection: 1; mode=block
Cache-Control: private, max-age=0
Content-Security-Policy: default-src 'none'; frame-ancestors
'none'; sandbox
Server:
Transfer-Encoding: chunked

{"name":"test space","uri":"/spaces/1"}
```

6.3 Encrypting sensitive attributes

A database in your datacenter, protected by firewalls and physical access controls, is a relatively safe place to store token data, especially if you follow the hardening advice in the last chapter. Once you move away from a database and start storing data on the client, that data is much more