yet so widely adopted that support for TLS 1.2 can be dropped completely. TLS 1.2 is still a very secure protocol, but for maximum security you should prefer cipher suites that offer *forward secrecy* and avoid older algorithms that use AES in CBC mode, because these are more prone to attacks. Mozilla provides recommendations for secure TLS configuration options (https://wiki.mozilla.org/Security/Server_Side_TLS), along with a tool for automatically generating configuration files for various web servers, load balancers, and reverse proxies. The configuration used in this section is based on Mozilla's Intermediate settings. If you know that your AS software is capable of TLS 1.3, then you could opt for the Modern settings and remove the TLS 1.2 support.

> **DEFINITION** A cipher suite offers ***forward secrecy*** if the confidentiality of data transmitted using that cipher suite is protected even if one or both of the parties are compromised afterwards. All cipher suites provide forward secrecy in TLS 1.3. In TLS 1.2, these cipher suites start with `TLS_ECDHE_` or `TLS_DHE_`.

To configure the connection to trust only the CA that issued the server certificate used by your AS, you need to create a `javax.net.ssl.TrustManager` that has been initialized with a `KeyStore` that contains only that one CA certificate. For example, if you're using the `mkcert` utility from chapter 3 to generate the certificate for your AS, then you can use the following command to import the root CA certificate into a keystore:

```
$ keytool -import -keystore as.example.com.ca.p12 \
```